

## Wi-Fi+4G Security Alarm System




## **About WiFi +4G Alarm System**

When any sensors such as door/window sensor, motion detector, water leakage detector, gas leakage detector, smoke detector, are triggered, the alarm host will send an alarm by pushing notification, calling and sending SMS to inform the user. At the same time, the on-site siren will emit a shrill alarm sound, ensuring your home and property security.




If there is no WiFi network, automatically switch to work with 4G. If WiFi network returns to work, it will switch to work with WiFi network again.



# Support adding various detectors








#### Each sensor name can be renamed

Door sensor: rename to know which door is open Remote control: rename to know who controlled the host



## **APP Smart Control Remote Arm/Disarm**

App smart control, realizing remote one click arm and disarm, alarm recording, information management. etc







## Timed Arming/Disarming

Customize automatic arm and disarm time to avoid repeated manual settings every day.



3 groups of automatic arm/disarm time can be set

#### **APP Push Message Alert**

When alarm sensor was triggered.the Vcare mobile APP will pop-up push message window and give out an alarm sound.





#### **FUNCTIONAL FEATURES**

- 1. APP supports Apple and Android systems
- 2. Bluetooth network configuration, faster and more stable
- 3. There is no limit to the number of alarm hosts that can be bound to each smartphone; each user of the alarm host can log in through administrator or general member mode, of which the administrator is limited to one person and the number of general members is unlimited.
- 4. Can set 5 groups of SMS alarm numbers and 5 groups of phone alarm numbers.
- 5. Supports 99 wireless defense zones, 30 fire defense zones, 8 emergency call defense zones, 8 medical rescue defense zones, 4 water leakage defense zones, and can be equipped with 20 remote controllers or access control keypads (the remote controller can also be used for emergency alarm); 4 wireless sirens can be configured.
- 6. Scan the QR code to add wireless accessories to the host, accurate, convenient and fast.
- 7. The default setting includes seven languages and voice switching (Chinese, English, Russian, Spanish, French, German, Italian).
- 8. Two-way intercom function;
- 9. Timed arming, timed disarming and timed stay function (each timer can be set for three groups of time);
- 10. WIFI failure and telephone network failure prompt function;
- 11. Door and window open reminder function;

- 12. Detector low battery prompt function, detector offline prompt function
- 13. Supports delayed alarm function, delayed arming and delayed disarming function (0-99 seconds optional);
- 14. When the host alarms, the srien sounding time can be selected (0-254 seconds or always sounding);
- 15. In addition to the APP, you can also remotely control the arming and disarming of the host by SMS or dial buttons during a phone call;
- 16. The host has the function of staying on defense (only valid for intrusion defense zones 1-99);
- 17. Can record 10 seconds of alarm voice;
- 18. External power failure/recovery alarm function (optional to turn on or off);
- 19. Remote arm/disarm siren sound prompt function (optional to turn on or off);
- 20. Remote controller arm/disarm SMS reminder function (optional to turn on or off);
- 21. Door and window opening/closing reminder function in disarmed state (optional to turn on or off).

## Recommended products

Package A



### Package A Giftbox Size



Box size:205mm x 205mm x 110mm

# **Accessory List**







Door/Window Sensor



**Emergency Button** 



**Emergency Button** 



Smoke Detector



Gas Detector



Water Leakage Detector



Wireless Keypad



Strobe Siren

#### TECHNICAL SPECIFICATIONS

Model No: PHcare

Wireless Radio Frequency: 433/868MHz

4G Frequency: LTE-FDD: B1/B3/B5/B8

B2/B3/B4/B5/B7/B8/B28/B66

LTE-TDD: B34/B38/B39/B40/B41

Wi-Fi: IEEE 802.11b/g/n.2.4GHz

Standby Power: ≤1W

Alarm Power: ≤2W

Internal Siren Volume: ≥80dB

Output Power Supply: DC5V 2A

Input Power Supply: AC100~240V

Standby Time: 8 hours

Battery: 3.7V 1000mAh Rechargeable Lithium Battery

Casing Materials: ABS Plastic

Operating Temperature: -20°C~+50°C

Relative Humidity: <95% (non-condensing)

Hub Dimensions: 145 x 145 x 30mm (L x W x H)