

Item	AHGQ-KDH Gasoline Sightseeing Bus	
Model	AHGQ-KDH-11	AHGQ-KDH-14
Seats (Including driver)	11	14
L*W*H (mm)	4740*1580*2050 (Excluding both side mirrors)	5400*1580*2050 (Excluding both side mirrors)
Total Weight (kg)	1250	
Front/Rear Tread (mm)	1340/1320	
Wheelbase (mm)	2880	
Min. Ground Clearance (mm)	130	
Max. Speed (km/h)	30	
Min. Tuming Radius (m)	≤5500	≤6500
Gradeability (Full Load) (%)	30%	25%
Engine	National VI Liuji Ll469/Ll4A15 EFI Engine	
Exhaust Emissions (L)	1.25/1.5	
Power (KW)	64/82	
Drive Mode	Mid-mounted engine and rear drive, with the strongest climbing ability	
Fuel Tank Volume (L)	50L high density polyethylene plastic fuel tank	
Frame	100*50mm double longitudinal beam welded frame, higher strength, safer and	
Suspension System	Front MacPherson independent suspension, rear longitudinal multi-plate leaf spring + hydraulic damping shock absorption	
Rear Axle	5.857 speed ratio, fully floating rear axle for commercial vehicles, strong load-bearing capacity, safe and reliable	
Braking System	Front disc and rear drum, dual-circuit hydraulic brake + vacuum booster	
Steering System	Foton rack and pinion steering gear + electronic power steering	

