




Superior Series (PS) 60mmx60mmx15mm




- Bearing Type : FLB, Ball Bearing
- Function Type (Optional): FG Signal, RD Signal, PWM
- Protection :
Auto Restart Protection, Polarity Reverse Protection
- Lead Wire :
UL 1061 AWG #26 OR Equivalent
Red Wire : Positive (+)
Black Wire : Negative (-)
Yellow Wire : FG Signal, RD Signal
Blue Wire : PWM



★ Dimensions Drawing



★ Performance Curves



Specification		Rated Voltage VDC	Operating Voltage VDC	Rated Current Amp	Input Current Amp	Input Power Watt	Rated Speed RPM	Air Flow		Air Pressure		Noise dBA
Model	Function Type							CMM	CFM	mmH ₂ O	InH ₂ O	
PSAD06015SL	P000/PF00	5	4.5-5.5	0.22	0.17	0.85	3600	0.54	19.2	2.99	0.12	27.5
PSAD06015SM	PR00/M000	5	4.5-5.5	0.36	0.28	1.40	4400	0.67	23.7	4.47	0.18	32.5
PSAD16010SL	P000/PF00	12	6-13.8	0.13	0.10	1.20	3600	0.54	19.2	2.99	0.12	27.5
PSAD16010SM	PR00/M000	12	6-13.8	0.17	0.13	1.56	4400	0.67	23.7	4.47	0.18	32.5
PSAD16010SH	MF00/MR00	12	6-13.8	0.22	0.17	2.04	5000	0.77	27.1	5.67	0.22	36.0
PSAD06015BL	P000/PF00	5	4.5-5.5	0.22	0.17	0.85	3700	0.56	19.8	3.20	0.13	28.5
PSAD06015BM	PR00/M000	5	4.5-5.5	0.36	0.29	1.45	4500	0.68	24.0	4.57	0.18	34.0
PSAD16010BL	P000/PF00	12	6-13.8	0.13	0.08	0.96	3700	0.56	19.8	3.20	0.13	28.5
PSAD16010BM	PR00/M000	12	6-13.8	0.17	0.13	1.56	4500	0.68	24.0	4.57	0.18	34.0
PSAD16010BH	MF00/MR00	12	6-13.8	0.22	0.17	2.04	5100	0.78	27.5	5.78	0.23	37.5

* Function type is optional
 * The data shows typical value at rated voltage
 * Sound level is measured at the distance of one meter from fan intake side
 * Specifications are subject to change without notice