

TECHNICAL DATA: MACH 4 R

Chassis	"ACTIO™" – Full chassis with oscillation • Articulated • Reversibility RGS™ • 4WD quadtrack	
Engine Type	Diesel direct injection Common Rail with counter rotating weight system Emissions Regulations: Stage 3B N° Cylinders: 4 - 16 Valves • Turbo Displacement (CC): 3769 Power kW/HP (97/68/CE): 72,1/98 Maximum engine revs: 2400 Torque max (Nm/revs): 330/1500 Cooling: Water Tank Capacity (litres): 50	
Transmission	32-speed synchronised gearbox: 16 forward + 16 reverse gears with synchronised shuttle	
PTO	Rear, independent 540/540E rpm, synchronised in all gears Oil-immersed multiplate clutch with progressive electro-hydraulic engagement	
Shaft	Profile 1" 3/8 with 6 splines with facilitated engagement	
Transmission clutch	Hydraulic control	
Drive disengagement	Electrohydraulic control on the front	
Hydraulic system	2 double-acting remote valves + oil return 2 pumps with independent circuits	
Rear power lift	With 3 point hitch Damping function for road transfer Adjustable lifting arms with Cat. 2 quick release couplings with adjustable width Height adjustable rear towing device "EEC" type - Front towing device Operating Pressure (bar): 160 Lifting capacity (Kg): 2400	
Steering	Hydraulic with 2 pistons	
Brakes	Hydraulic front/rear oil bath disc brakes; independent hydraulic rear steering brakes Automatic emergency and parking oil bath brakes on transmission	
Platform	Suspended on Silent Block	
Weight in order of speed:	With roll bar (Kg): 3150	With AIR cab (Kg): 3300

STANDARD FEATURES

- Reversible driving position with servo-assisted reversibility
- Rear or front/rear differential lock with electrohydraulic control
- Suspended controls
- Adjustable steering wheel with reverser embedded
- Adjustable, suspension seat with safety belt with automatic retractors
- Rear safety roll bar
- Digital multifunctional dashboard with display and diagnostic function
- Engine rpm control with double memory (Cruise control)
- Battery
- Battery isolation switch
- Electrical power point
- Start inhibit switch on shuttle reverser, PTO selector and seat
- Adjustable rear work spotlight

OPTIONAL

- "AIR" cab FOPS and ROPS- certified cab
- Soundproof platform with thermal insulation
- Roof with rear skylight
- 2 rear and 2 front work LED spotlights
- Air conditioning system with cooler and heat exchanger and inner air re-circulation
- Additional front/rear working LED lights
- Suitable for category 4

- E-DRIVE transmission with shuttle control on steering wheel and electro-hydraulic range shift
- Hydraulic power lift with electronic draft and position control power lift with damping
- Higher 3 point linkage
- Support with six front ballast weights
- Hydraulic third hitch and vertical tie-rod
- Front power lift
- Gearbox with PTO 540-1000 rpm
- Gearbox with PTO 540-540S rpm
- Hydraulic system with hydraulic pump up to 51 liters/min
- Electro-proportional hydraulic system controlled by joystick with double driver safety system and integrated control unit with user-adjustable settings
- 11 rear quick couplings - UNIFLEX hydraulic suspension on the rear power lift with control and settings on display
- Quick release couplings Cat. 1
- Pneumatic seat
- Fabric Grammer seat with air suspension and load display, reclining backrest, lumbar support
- Front bullbar
- Front lamp guards
- ACS fan with reversible air flow to clean the radiator
- "Superbrake" braking system
- Steering brakes
- Couple of pads for front tracks
- Road approval up to 40 Km/h (25 mp/h)

DIMENSIONS

