KÖMMERLING WORLDWIDE





Kömmerling Chemische Fabrik GmbH Zweibrücker Straße 200 D-66954 Pirmasens 0049 6331 562000 Phone 0049 6331 561999 Fax e-mail: info@koe-chemie.de www.koe-chemie.de

Adhesives & Sealants LLC 2001 West Washington St US-South Bend, IN 46628 001 574 246 5000 Phone e-mail: info@royaladhesives.com

www.royaladhesives.com

ROYAL Europe Holding GmbH China Representative Office 1007 Air China Plaza, 36 Xiaoyun Road, Chaoyang District CN - Beijing 100027 China 0086 10 6461 9988 Phone 0086 10 6461 9900 Fax e-mail: info@adcochina.net www.koe-chemie.com

Kommerling UK Limited 27 Riverside Way, Uxbridge GB-Middlesex UB8 2YF United Kingdom

0044 1895 465 600 Phone

www.kommerlinguk.com

0044 1895 465 617 Fax

Kömmerling Chimie Sàrl 7, Rue des Corroyeurs F-67200 Strasbourg 0033.3.88.28.83.59 Phone 0033.3.88.28.22.23 Fax e-mail: info.france@koemmerling.com e-mail: enquiries@kommerlinguk.com www.koe-chemie.fr

> Kömmerling Chemische Fabrik GmbH Russia Representative Office ul. Kozjubinskogo, 4 - Building 3 RU-121351 Moscow 007 495 984 2174 Phone e-mail: info.ru@koemmerling.com www.koe-chemie.com



ADHESIVES AND SEALANTS FOR THE MARINE INDUSTRY











Bonding and Sealing for outside applications



Körapop 950 Marine

1-part elastic moisture curing hybrid adhesive and sealant, multi purpose, good

resistance against UV radiation, humidity and weathering, solvent free, 5 days overpaintable

Körapop 954 Marine

1-part elastic moisture curing hybrid adhesive and sealant, good resistance against UV radiation, humidity and weathering, solvent free, good sagging properties, high strength

Ködisil A

1-part elastic moisture neutral curing silicone adhesives and sealant, very good resistance against UV radiation humidity and weathering, solvent free, anti fungal, paint compatible to DIN 525452

Deck caulking



Köraflex 996

2-part sealant, very good resistance against UV radiation humidity and weathering, solvent-free, fast reaction

Bedding of deck floorings



Körapur 928 Marine

1-part elastic moisture curing PUR adhesive and sealant, good resistance to humidity and weathering, overpaintable after curing, long open time, high strength, easy to spread

Körapur 672 O

2-part solvent-free liquid PUR adhesive, low sensitivity to moisture, high strength

2-part solvent-free PUR adhesive, low sensitivity to moisture,

Structural Bonding



Körapur 940 Marine

1-part and 2-part elastic moisture curing PUR adhesive and sealant, good resistance to humidity and weathering, overpaintable after curing, long open time, high strength

Körapop 954 Marine

1-part and 2-part elastic moisture curing hybrid adhesive and sealant, good resistance to humidity and weathering, solventfree, good sagging properties, high strength



2-part PUR construction adhesive, low sensitivity to moisture, solvent-free

Körapur 840 💿



2-part PUR construction adhesive, good impact resistance, solvent-free

2-part epoxy construction adhesive, solvent-free

Bonding and Sealing below the waterline



Körapur 925 Marine

1-part elastic moisture curing, multi purpose PUR adhesive and sealant, good resistance to humidity and weathering, overpaintable after curing

Körapur 940 Marine



1-part elastic moisture curing PUR adhesive, good resistance to humidity and weathering, overpaintable after curing, long open time, high strength

Glazing applications

Körapur 177

1-part elastic moisture curing PUR adhesive, high strength, good resistance to humidity and weathering, overpaintable after curing

Körapop 954 Marine

1-part elastic moisture curing hybrid adhesive and sealant, good resistance to humidity and weathering, good sagging properties, high strength, solvent free

Ködiglaze SDG

2-part solvent-free silicone adhesive, high strength, no black primer needed

Ködisi A

1-part elastic moisture neutral curing silicone sealant, very good resistance against UV radiation humidity and weathering, solvent free, anti fungal, paint compatible to DIN 525452

1-part elastic moisture neutral curing silicone sealant, very good resistance against UV radiation humidity and weathering, solvent free, long open time, very high flexibility