



FLUX flow meters with
new digital display unit
FLUXTRONIC®

New!

- New menu-driven control panel
- All data will be maintained when replacing the battery due to currentless memory
- 4 safety levels with PIN setting
- Three additional outlets



The reliable FLUX flow meters FMC and FMJ (constructed according to the principle of rotating disc) or FMO (constructed to the principle of oval rotors) offers in combination with our drum pumps everything which is needed for the fast and secure emptying of drums and containers.


Basically there are two operation modes available. In normal mode the measured volume will be displayed. The automatic mode can be used for batch filling of preset volumes. As soon as the batch filling process is finished there is the possibility to send two signals which can be used for a solenoid valve or a drive motor.

Now FLUX flow meters will be delivered serially with the new digital display unit FLUXTRONIC®.

FLUX flow meters with the new digital display unit FLUXTRONIC®



Special features and benefits:

- New menu-driven control panel
- All data will be maintained when replacing the battery due to currentless memory
- 4 safety levels with PIN setting
- Three additional outlets:
 - Filling operation OK
 - Error display
 - Transmission of pulses
- Also for the explosion proof area in zone 1 
- Special Exit key
- Single configuration of keys by one function only



Further information
on FLUX flow meters
and amplifiers for
preset batch control
you will find in the
special brochures
FMC/FMO
and Accessories

FLUX-GERÄTE GMBH
Talweg 12 · D-75433 Maulbronn
Tel +49 (0)7043 101-0 · Fax +49 (0)7043 101-555
info@flux-pumpen.de · www.flux-pumpen.de