


OKS 2621

Contact Cleaner, Spray



Description

OKS 2621 is a contact cleaner to remove soiling that can cause creepage currents.

Applications

- Removal of loose oxide and electrode-erosion residues, dust deposits or creepage currents which cause soiling in moving contact areas such as motor-vehicle ignition distributors, relay contacts, resistance or potentiometer slideways, in static contact areas such as motor-vehicle spark plugs, plug-in connections, sliding and screw connections, in or on electrical and electronic equipment or devices of all kinds

Advantages and benefits

- Highly effective due to outstanding cleaning properties
- Broad range of uses for all maintenance and customer service work in electrical sector
- Fast evaporation after striking surface

Branches

- Logistics
- Municipal services
- Rail vehicle technology
- Glass and foundry industry
- Iron and steel industry
- Maintenance and servicing
- Rubber and plastic processing
- Chemical industry
- Shipbuilding and marine technology
- Paper and packaging industry
- Plant and machine (tool) engineering

Application tips

Disconnect voltage and shunt electrostatic charge prior to application. Spray on areas to be cleaned until the desired cleanliness is reached. Components are generally considered to be compatible with plastics, but because of the big variety of materials we recommend you to check the resistance before use.

Packaging

- 400 ml Spray



OKS 2621

Contact Cleaner, Spray

Technical data

	Standard	Conditions	Unit	Value
Main components				
base oil				aliphatic hydrocarbons
Application related technical data				
colour				colourless
density (at 20°C)	DIN EN ISO 3838		g/cm ³	0.72

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47

82216 Maisach

+49 8142 3051 - 500

info@oks-germany.com

www.oks-germany.com



The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark

Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com

Our Customer and Technical service will be pleased to help should you have any further questions.