

Model 5200

Power Supply

DESCRIPTION

The Model 5200 is a basic unregulated power supply that is designed for use with Magtrol's Hysteresis Brakes and Clutches. The 5200 is available in either 12, 24 or 90 VDC voltages, corresponding to the available hysteresis brake/clutch coil voltage options. Braking control is enabled via a 10-turn potentiometer and adjustment knob located on the front panel.



SPECIFICATIONS

	5200-1	5200-2	5200-3
Brake Voltage	0 to 90 VDC	0 to 24 VDC	0 to 12 VDC
Current Range	0 to 300 mA	0 to 1000 mA	0 to 1500 mA
Braking Control	10-turn potentiometer		
Brake Fuse (5 × 20 mm)	UL/CSA 0.400 A 250V SB IEC 0.315 A 250V T	UL/CSA 1.25 A 250V SB IEC 1.00 A 250V T	UL/CSA 2.00 A 250V SB IEC 1.60 A 250V T
Line Fuse (5 × 20 mm)	120 V: UL/CSA 1.0 A 250V SB 240 V: IEC 0.4 A 250V T		
Power Requirements	100 VA		
Voltage Requirements	120/240 VAC 50/60 Hz		

Due to the continual development of our products, we reserve the right to modify specifications without forewarning.



www.magtrol.com

MAGTROL INC

70 Gardenville Parkway
Buffalo, New York 14224 USA
Phone: +1 716 668 5555
Fax: +1 716 668 8705
E-mail: magtrol@magtrol.com

MAGTROL SA

Centre technologique Montena
1728 Rossens/Fribourg, Switzerland
Phone: +41 (0)26 407 3000
Fax: +41 (0)26 407 3001
E-mail: magtrol@magtrol.ch

Subsidiaries in:

Great Britain
Germany • France
China • India
Worldwide Network
of Sales Agents

