



# BlueSky LS R 2/Y-Y

Speaker cable round

### APPLICATION

Top quality connection between amplifier and speaker box in mobile stages

### CONSTRUCTION


<b>Conductor</b>	Stranded bare copper
<b>Stranding</b>	class 5, class 6 or 0,10 mm
<b>Insulation</b>	Special PVC
<b>Colours</b>	bk, rd
<b>Jacket</b>	Soft PVC
<b>Jacket colour</b>	black-matt surface (RAL 9005)
<b>Surface marking</b>	acc to customer spec.

### TECHNICAL DATA

<b>Insulation resistance</b>	min 20 MΩm*km
<b>Conductor resistance</b>	acc to VDE 0295
<b>Temperature range static</b>	-30°C to +70°C
<b>Temperature range operating</b>	-10°C to +70°C

### REMARKS

Other specially versions possible (OFC, halogenfree)



No of Cores + Cross Section mm <sup>2</sup>	Copper Index (kg/km)	Weight (appr. kg/km)	Width / Outer Ø ca. mm	P/N
class 5:				
2 x 1,5			7,20	06012902
4 x 1,5			8,60	06012914
8 x 1,5			10,80	06012908
2 x 2,5			8,20	06013002
4 x 2,5			10,20	06013004
8 x 2,5			15,80	06013008
2 x 4,0			9,20	06013051
4 x 4,0			12,80	06013054
2 x 6,0			16,60	06013070
			11,20	06012862
class 6:				
2 x 1,5			7,00	06012962
2 x 2,5			7,80	06013047
4 x 2,5			8,80	06013000
8 x 2,5			15,80	06013021
2 x 4,0			9,50	06013072
4 x 4,0			11,20	06013090
8 x 4,0			16,60	06013069
0,10 mm:				
2 x 1,5			7,20	06018075
2 x 2,5			8,00	06013019
4 x 2,5			10,60	06013024
8 x 2,5			12,50	06013049
2 x 4,0			10,80	06013062
4 x 4,0			12,80	06013064