

# Precise and simple label dispensing for a great price

**NEW**

## HS60+



## VS120



## VS180+



The new label dispensers succeed through easy handling and affordability. cab offers two designs for dispensing in correct position:

- the HS dispenses the label horizontal - bottom leading
- the VS dispenses the label vertical - top leading

The basic version is made for automatic operation. After removal of the label the next label is dispensed automatically.

The „+“ models have an additional operation panel with the following functions:

- Dispensing label automatically or on demand
- Slow or fast feed rate
- Label counter from 1 - 9,999
- Peripheral connection utilizing an external signal for „dispensing on demand“.

The dispensers are available in three different widths. Max. width for narrow labels up to 60 mm, medium labels up to 120 mm and large labels up to 180 mm.



Scan this QR code with your smartphone and learn more about HS/VS series.

Common technical data		HS/VS	HS+/VS+	
Label dispensing speed up to mm/sec		100	200	
Dispensing direction		HS horizontal / VS vertical		
Label orientation		HS bottom leading / VS top leading		
Labels		on rolls, standard or die cut, fan-folded optional		
Material		Paper, textiles, plastics also transparent		
Label roll:	total diameter up to mm	200		
	Core diameter mm	38 - 76		
	Weight max. kg	4		
	Winding direction	outside or inside		
<b>Rewinder</b>				
Liner	total diameter up to mm	155		
<b>Label sensor</b>				
Scanning	leading edge of label	microswitch trigger with photocell		
Position of scanning		leading edge of the label		
Adjustable distance to leading edge mm		5 - 55		
Pre-dispense:	peel-off plate sensor mm	4 - 18		
<b>Operation</b>				
Selector switch	automatic peel-off or on-demand peel-off	-	■	
Control button	peel-off on-demand	-	■	
Selector switch	feed supply rate	-	slow / fast	
LCD display	label counter	-	1 - 9999	
Control button	reset label counter	-	CLR	
Display	dispensing via external signal	-	■	
<b>Interface</b>				
Peripheral connection for peel-off on-demand via external signal		-	■	
<b>Operating data</b>				
Power supply		100 - 240 V ~ 50/60 Hz, PFC		
Power consumption		operation / stand by max. 30 W / 5 W		
Temperature / humidity:		operation +5 - 40°C, / 10 - 85% not condensing		
		storage +0 - 60°C, / 20 - 80% not condensing		
		transport -25 - 60°C, / 20 - 80% not condensing		
Noise level		< 60 dB		
Approvals		CE, FCC class A, CB, CCC, UL		
Device specific dimensions		HS/VS60	HS/VS120	HS/VS180
<b>Label dimensions</b>				
Width of labels	including liner mm	8 - 65	20 - 120	80 - 180
Height of labels	one-wide mm	5 - 300	8 - 600	20 - 600
	multi-wide mm	5 - 110	8 - 110	20 - 110
<b>Hardware dimensions</b>				
Height x depth without material mm		250 x 360	250 x 360	250 x 360
Width mm		180	230	300
Weight kg		3,3	3,6	4,0

- *Headquarters in Germany*
- *cab subsidiaries*  
*350 distribution partners*  
*in more than 80 countries.*

*cab is represented in every active commercial center - worldwide.*



For elaborate data, please go to [www.cab.de](http://www.cab.de)

#### Germany

cab Produkttechnik  
GmbH & Co KG  
Postfach 1904  
76007 Karlsruhe  
Wilhelm-Schickard-Str. 14  
76131 Karlsruhe  
Telefon +49 721 6626-0  
Telefax +49 721 6626-249  
[www.cab.de](http://www.cab.de)  
[info@cab.de](mailto:info@cab.de)

[Representatives in other countries on request.](#)

#### France

cab technologies s.a.r.l.  
67350 Niedermodern  
Téléphone +33 388 722 501  
[www.cab.de/fr](http://www.cab.de/fr)  
[info.fr@cab.de](mailto:info.fr@cab.de)

#### USA

cab Technology Inc.  
Tyngsboro MA, 01879  
Phone +1 978 649 0293  
[www.cab.de/us](http://www.cab.de/us)  
[info.us@cab.de](mailto:info.us@cab.de)

#### South Africa

cab Technology (Pty.) Ltd.  
2125 Randburg  
Phone +27 11-886-3580  
[www.cab.de/za](http://www.cab.de/za)  
[info.za@cab.de](mailto:info.za@cab.de)

#### Asia 亚洲

cab Technology Co, Ltd.  
希愛比科技股份有限公司  
Junghe, Taipei, Taiwan  
Phone +886 2 8227 3966  
[www.cab.de/tw](http://www.cab.de/tw)  
[info.asia@cab.de](mailto:info.asia@cab.de)

#### China 中国

cab (Shanghai) Trading Co., Ltd  
铠博(上海)贸易有限公司  
Phone +86 21 6236-3161  
[www.cab.de/cn](http://www.cab.de/cn)  
[info.cn@cab.de](mailto:info.cn@cab.de)

This documentation and any translations hereof are the property of cab GmbH & Co KG.

The replication, processing, reproduction or distribution in whole or in parts requires our prior written consent. © Copyright by cab.

All delivery, design and technical specifications are compiled to the best of our current knowledge and are subject to change without prior notice.