



3-phase Power Supply

Key Features

- Switching Power Supply
- 480W Output Power
- Wide Input Voltage Range:
 - 320 – 575V AC (3-phase operation)
 - 360 – 575V AC (2-phase operation)
- Output: 24V DC, 20A
- Overcurrent and Overvoltage Protection
- DIN-rail mount
- RoHS Compliant
- Approvals:
 - CE Marked
 - UL 508 Listed
 - UL 60950-1 Recognized
 - EN60204, EN61558-2-17, EN60950, EN61000-3-2
 - DIN VDE 0100-410, DIN VDE 0106-1010, DIN 57100-410, DIN VDE 0106-101



Specifications

Part Number		PSSR-TJ24	
Output Capacity		480W	
Input	Input Voltage	3-phase	320 - 575V AC
		2-phase	360 - 575V AC
	Input Current (maximum)	400V AC	3 x 1.1A
		480V AC	3 x 0.8A
	Frequency	45Hz - 65Hz	
	Inrush Current (cold start)	21A max	
	Leakage Current (at no load)	<3.5mA	
Typical Efficiency	91%		
Output	Output Current Rating	20A	
	Voltage Adjustment	22.5 - 29.5V	
	Output Holding Time	10ms typical	
	Starting Time	1s	
	Line Regulation (static)	1.0% max	
	Load Regulation (dynamic)	2.0% max	
	Ripple Voltage	< 10mVpp	
	Overcurrent Protection	125%, auto reset	
	Overvoltage Protection	35V DC max	
	Operation Indicator	LED (green)	
Parallel Operation		Yes	
Insulation Resistance	Input / Output	2kV AC	
	Input / Ground	2kV AC	
	Output / Ground	500V DC	
Operating Temperature		-25 to +70°C	
Storage Temperature		-40 to +85°C	
Operating Humidity		95% max (at 25°C, no condensation)	
Vibration Resistance		<15Hz amplitude +/- 2.5mm in accordance with IEC 60068-2-6 15 to 150Hz, 2.3g, 90 min.	
Shock Resistance		30g in all directions in accordance with IEC 60068-2-27	
Standards & Approvals		EN55011 (Class B), EN61000-3-2, EN61000-3-3, EN55024, EN61000-6-2, IEC61000-4-2,3,4,5,6,11, UL 508 (listed), UL 60950-1 (Recognized)	



Specifications can't on next page

Specifications con't

Harmonic Directive	EN 61000-3-2
Weight (approx.)	approx. 2kg
Connection	Screw terminals
IP protection	IP20
Dimensions H x W x D (mm)	130 x 115 x 152.5
Dimensions H x W x D (inches)	5.12 x 4.53 x 6.00

Accessories

Item	Description	Part Number
	DIN rail (1000mm)	BNDN1000
	DIN rail end clip	BNL6

Dimensions (mm)

