









Maximum length of Workpiece : Maximum width of cut : Maximum cutting height :

: up to 16 meters : 800mm : approx. 170mm

The installation consists of:

### 1 Infeed table for TigerStop TSL Automatic heavy duty pusher left or righthand

Total length Width of table : up to 18 meters : 600 / 700mm

## 1 TigerStop TSL Heavy Duty Pushfeed and Stop

Working length (stroke) Drive DC Servo motor with gearbox Feed speed

Précision Guide profile (fence Drive system Load : up to 16 meters
: approx 1,1Kw
: maximum 40 meters per minute (Depends on load)
: +/- 0.4mm
: 180mm height
: steel toothed rack

: up to 600 kg weight of work piece

### 1 Cross cut saw (hydropneumatic) model TS800

Model : undertable cross cut saw with pneumatic top clamp and side guide Sawblade diameter : 550mm : 70 x 700mm , 100 x 500mm 140 X 350mm Cutting capacity (examples) Cutting height : maximum 170mm : 5,5kw or 7,5kw Motor power Working height : 900mm Diameter of dust exhaust : 2 x Ø 120mm The machine is equiped with a motor brake system and works with 2 hand push button operation or fully automatic with TigerStop pusher

# 1 Outfeed table : lengths up to 18 meters

#### **Extra options**

TigerOptimizer HandyScan Labelprinter LineCut High performance optimising software level 3
Patented defecting device by laser line
for part identification 50 or 100mm wide labels
on screen display of cutlist and description of parts
With 15 inch touch screen



TigerStop BV Postbus 11 7640AA Wierden The Netherlands

tel: + 31 546 57 51 71 fax: + 31 546 57 77 22 www.TigerStop.com info@tigerstop.nl