

KEMPERDUR CL Chips



Uses

- For the decorative surface treatment of
 - KEMPERDUR Deko
 - KEMPERDUR Deko 2K
 - KEMPERDUR HB thick coating

Characteristics

- Decorative
- Slip-reducing
- Base: PVC and PVA

Pack sizes

1 kg

Size of Chips 2 - 5 mm

Shelf Life

Store in a dry environment.

Properties

Form	solid
Colour	White
	black
	light grey

* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

Usage guide

Depending on the chip density, at least 30 g/m²

CE marking

Component to 4	ETA 03/0043
	ETA 03/0044

Application

Apply and spread KEMPERDUR surfacings. Use a chip blast gun to blow chips into the fresh coat or scatter them by hand. KEMPERDUR Deko 2K or KEMPERDUR HB thick coating can be sealed after 12 hours and KEMPERDUR Deko after 72 hours with KEMPERDUR Finish. Only apply when the substrate and ambient temperatures are at least +5 °C.

Personal protective equipment should be worn.

Disposal

solid	EAK 17 02 03
-------	--------------

General information

No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30